Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

DBS Cable
Series 59 and Series 6

Jameco Part Number 234177 (1829AC-010-500)

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

Series 59 • 20 AWG Solid .032″ Bare Copper-covered Steel • Duobond® II + 40% Aluminum Braid Shield

Gas-injected Foam Polyethylene Insulation • Black PVC Jacket

80°C	**1830A**	NEC: CATV CM CEC: CM	U-1000	U-304.8	24.0	10.9	20 AWG (solid) .032″ BCCS 44.5Ω/M′ 146.0Ω/M′	.144	3.66	Duobond II + 40% Aluminum Braid 17.0Ω/M′ 55.8Ω/km	.237	6.02	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250	.8 1.8 3.4 5.2 6.5 7.0 7.7 9.3 10.3 11.9	2.5 6.0 11.0 17.1 21.4 22.9 25.2 30.5 33.8 39.0

Sweep tested 950 MHz to 2.25 GHz.

Series 6 • 18 AWG Solid .040″ Bare Copper or Bare Copper-covered Steel Cond. (see below) • Duobond II + 60% Aluminum Braid Shield

Gas-injected Foam Polyethylene Insulation • PVC Jacket (Black, Gray or White)

80°C	**1829A**	NEC: CATV CM CEC: CM	U-1000▲ 1000▲	U-304.8 304.8	31.0 31.0	14.1 14.1	18 AWG (solid) .040″ BCCS 28.0Ω/M′ 91.9Ω/km	.180	4.57	Duobond II + 60% Aluminum Braid 9.0Ω/M′ 29.5Ω/km	.270	6.86	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.9 8.4 10.1	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.9 27.6 33.1

Sweep tested 950 MHz to 2.25 GHz.

▲1000 ft. and U-1000 ft. put-ups also available in Beige.

80°C	**1829AC**	NEC: CATV CM CEC: CM	U-1000 1000	U-304.8 304.8	31.0 31.0	14.1 14.1	18 AWG (solid) .040″ BC 6.4Ω/M′ 21.0Ω/km	.180	4.57	Duobond II + 60% Aluminum Braid 9.0Ω/M′ 29.5Ω/km	.270	6.86	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250 3000	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.9 8.4 10.1 11.0	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.9 27.6 33.1 36.1

Sweep tested 950 MHz to 2.25 GHz.

Gas-injected Foam Polyethylene Insulation • Black Polyethylene Jacket

Burial 80°C CoreGuard®	**1829B** new		1000	304.8	27.0	12.3	18 AWG (solid) .040″ BCCS 28.0Ω/M′ 91.9Ω/km	.180	4.57	Duobond II + 60% Aluminum Braid 9.0Ω/M′ 29.5Ω/km	.270	6.86	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.9 8.4 10.1	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.9 27.6 33.1

Sweep tested 950 MHz to 2.25 GHz.

Burial 80°C CoreGuard®	**1829BC** new		1000	304.8	28.0	12.7	18 AWG (solid) .040″ BC 6.4Ω/M′ 21.0Ω/km	.180	4.57	Duobond II + 60% Aluminum Braid 9.0Ω/M′ 29.5Ω/km	.270	6.86	75	83%	16.2	53.1	5 55 211 500 750 862 1000 1450 1800 2250 3000	.5 1.4 2.6 4.1 5.1 5.5 6.0 7.9 8.4 10.1 11.0	1.6 4.6 8.5 13.5 16.7 18.0 19.7 25.9 27.6 33.1 36.1

Sweep tested 950 MHz to 2.25 GHz.

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance